

Attorney Docket No. 10559-391001  
Serial No.: 09/745,104  
Amendment dated January 20, 2004  
Reply to Office Action dated November 19, 2003

Amendment to the Claims:

This listing of claims replaces all prior versions, and listings, of claims in the application:

---

1. (Currently amended) A method comprising:

defining, within a computer program, conditions for a

hardware loop;

first propagating a first of said loop conditions of [[a]]  
said hardware loop via a first pipeline of a pipelined  
processor; and

second propagating in parallel with said first propagating  
a second of said loop conditions via a second pipeline of the  
pipelined processor.

2. (Currently amended) The method of claim 1, further comprising:

writing the loop conditions to a first set of registers  
prior to propagating the loop conditions and using said  
registers to begin calculating parameters based on said loop  
conditions prior to said propagating, and

writing the loop conditions to a second set [[or]] of  
registers after propagating the loop conditions.

3. (Canceled)

Attorney Docket No. 10559-391001  
Serial No.: 09/745,104  
Amendment dated January 20, 2004  
Reply to Office Action dated November 19, 2003

A4  
4. (Currently amended) A method of claim 1, further comprising propagating a third of said loop conditions via a third pipeline.

5. (Original) The method of claim 2, further comprising generating the loop conditions of the hardware loop prior to writing the loop conditions to the first set of registers.

6. (Original) The method of claim 5, wherein generating the loop conditions comprise calculating at least one of the loop conditions from program counter relative data in a loop setup instruction.

7. (Currently amended) A method comprising:  
first calculating a first loop condition of a hardware loop from a loop setup instruction using a first arithmetic logic unit in a first pipeline; and  
second calculating a second loop condition of the hardware loop from the loop setup instruction using a second arithmetic logic unit in a second pipeline; and  
using results of said first calculating and said second calculating for propagating loop information to hardware

Attorney Docket No. 10559-391001  
Serial No.: 09/745,104  
Amendment dated January 20, 2004  
Reply to Office Action dated November 19, 2003

A4 registers associated with calculating parameters of the hardware  
loop; and

beginning to calculate said parameters using said hardware  
loop, based on said loop conditions, prior to said propagating.

8. (Original) The method of claim 7, further comprising writing the first and second loop conditions to a first set of registers.

9. (Original) The method of claim 7, further comprising:  
calculating a third loop condition of the hardware loop from the loop setup instruction using a third arithmetic logic unit in a third pipeline; and

writing the first, second and third loop conditions to a first set of registers.

10. (Original) The method of claim 7, wherein calculating the first loop condition and calculating the second loop condition occur in parallel.

11. (Original) The method of claim 8, further comprising propagating the first loop condition to a second set of registers via a first pipeline.

Attorney Docket No. 10559-391001  
Serial No.: 09/745,104  
Amendment dated January 20, 2004  
Reply to Office Action dated November 19, 2003

A4  
12. (Original) The method of claim 11, further comprising propagating the second loop condition to the second set of registers via a second pipeline.

13. (Currently amended) An apparatus comprising:  
a first pipeline including a first arithmetic logic unit  
and a second pipeline including a second arithmetic logic unit,  
and

a control unit coupled to the pipelines, the control unit adapted to:

obtain loop setup instructions for a hardware loop  
from a computer program;

first calculate a first loop condition of a hardware loop from [[a]] one of said loop setup instructions using the first arithmetic logic unit in the first pipeline; and

second calculate a second loop condition of the hardware loop from a loop setup instruction using the second arithmetic logic unit in the second pipeline, in parallel with said first calculate.

14. (Original) The apparatus of claim 13, the apparatus further comprising a first set of registers coupled to the

Attorney Docket No. 10559-391001  
Serial No.: 09/745,104  
Amendment dated January 20, 2004  
Reply to Office Action dated November 19, 2003

A4  
control unit, wherein the control unit is further adapted to write the first and second loop conditions of the hardware loop to the first set of registers.

15. (Original) The apparatus of claim 14, the apparatus further comprising a third pipeline coupled to the control unit, the third pipeline including a third arithmetic logic unit; the control unit further adapted to:

calculate a third loop condition of the hardware loop from the loop setup instruction using the third arithmetic logic unit in the third pipeline; and

write the first, second and third loop conditions of the hardware loop to the first set of registers.

16. (Original) The apparatus of claim 14, the apparatus further comprising a second set of registers coupled to the control unit, wherein the control unit is further adapted to propagate at least one of the loop conditions to the second set of registers via the first pipeline.

17. (Original) The apparatus of claim 16, the control unit further adapted to propagate at least one of the loop conditions to the second set of registers via the second pipeline.

Attorney Docket No. 10559-391001  
Serial No.: 09/745,104  
Amendment dated January 20, 2004  
Reply to Office Action dated November 19, 2003

A4  
18. (Original) The apparatus of claim 15, the apparatus further comprising a second set of registers coupled to the control unit, the control unit further adapted to:

propagate at least one of the loop conditions to the second set of registers via the first pipeline;

propagate at least one of the loop conditions to the second set of registers via the second pipeline; and

propagate at least one of the loop conditions to the second set of registers via the third pipeline.

19. (Original) The apparatus of claim 14, wherein the first set of registers are speculative registers.

20. (Original) The apparatus of claim 13, wherein at least one of the pipelines is a data address generation pipeline.

21. (Original) The apparatus of claim 13, wherein at least one of the pipelines is a system pipeline.

22. (Currently amended) An apparatus comprising a set of registers, a first pipeline, and a second pipeline; and

Attorney Docket No. 10559-391001  
Serial No.: 09/745,104  
Amendment dated January 20, 2004  
Reply to Office Action dated November 19, 2003

A4  
a control unit coupled to the set of registers, the first pipeline and the second pipeline, the control unit adapted to:  
first propagate at least one loop condition of a hardware loop to the set of registers via the first pipeline; and  
second propagate at least one loop condition of the hardware loop to the set of registers via the second pipeline;  
and  
begin calculating using said hardware loop, prior to completing said first and second propagate.

23. (Original) The apparatus of claim 22, wherein the set of registers are a second set of registers, the apparatus further including a first set of registers coupled to the control unit, wherein the control unit is further adapted to:  
write the loop conditions of the hardware loop to the first set of registers prior to propagating at least one of the loop conditions to the second set of register

24. (Original) The apparatus of claim 22, wherein at least one of the pipelines is a data address generation pipeline.

25. (Original) The apparatus of claim 22, wherein at least one of the pipelines is a system pipeline.

Attorney Docket No. 10559-391001  
Serial No.: 09/745,104  
Amendment dated January 20, 2004  
Reply to Office Action dated November 19, 2003

A4  
26. (Currently amended) A system comprising:  
a static random access memory device;  
a processor coupled to the static random access memory device, wherein the processor includes a first set of registers, a first pipeline, a second pipeline, and a control unit adapted to:

first calculate a first loop condition of a hardware loop from a loop setup instruction using a first arithmetic logic unit in the first pipeline,

second calculate a second loop condition of the hardware loop from the loop setup instruction using a second arithmetic logic unit in the second pipeline, in parallel with the first calculate; and

write the first and second loop conditions of the hardware loop to the first set of registers.

27. (Original) The system of claim 26, the processor including a third pipeline, the control unit further adapted to:  
calculate a third loop condition of the hardware loop from the loop setup instruction using a third arithmetic logic unit in the third pipeline; and



Attorney Docket No. 10559-391001  
Serial No.: 09/745,104  
Amendment dated January 20, 2004  
Reply to Office Action dated November 19, 2003

A4  
write the first, second and third loop conditions of the hardware loop to the first set of registers.

28. (Currently amended) A system comprising:

a static random access memory device;

a processor coupled to the static random access memory device, wherein the processor includes a first set of registers, a second set of registers, a first pipeline, a second pipeline, and a control unit adapted to:

write loop conditions of a hardware loop to the first set of registers;

propagate at least one of the loop conditions to the second set of registers via the first pipeline; and

propagate at least one of the loop conditions to the second set of registers via the second pipeline; and

begin calculating data using said hardware loop prior to completing said first and second propagate.

29. (Original) The system of claim 28, the processor further including a third pipeline, the control unit further adapted to propagate at least one of the loop conditions to the second set of registers via the third pipeline.

Attorney Docket No. 10559-391001  
Serial No.: 09/745,104  
Amendment dated January 20, 2004  
Reply to Office Action dated November 19, 2003

A4 30. (Original) The system of claim 28, the control unit further adapted to:

calculate a first loop condition of the hardware loop from a loop setup instruction using a first arithmetic logic unit in the first pipeline; and

calculate a second loop condition of the hardware loop from the loop setup instruction using a second arithmetic logic unit in the second pipeline.